

L551:N172			
Code	(4-)	P	(G4)



Premier5

Decorative Textured Ceiling & Wall Finish

A decorative finish that can be applied to ceiling or walls to create a variety of textured patterns.

Technical data sheet

Features

- Warm or cold water mix for convenience
- Easy to work with, saving time
- Extended working time, less wastage
- Covers rough surfaces, no need to pre-smooth
- Excellent definition to create any pattern

available in
25kg bag



Surface Preparation

All surfaces must be clean, sound and dry prior to application. For the application onto papered flaky or distempered surfaces, remove previous decorative material and seal first using the appropriate Instarmac primer, diluted as specified.

Mixing

Slowly add Wondertex Premier 5 to hot, warm or cold water at a ratio of 1kg per 500ml. Stir in briskly and leave to stand for a few minutes. Mix to the required consistency by adding more powder. Always leave Wondertex Premier 5 to stand for a few minutes before application.

Application

Apply liberally in one metre strips, with a brush or roller, across the ceiling width or from top to bottom of walls. Texture an area of approximately 1m² at any one time while still wet. Once applied, the product's working time is up to 15 minutes.

Application to Plasterboard

Taping using white perforated tape. Apply paste to the joints and to 50mm either side. Press tapes firmly over joint with caulking tool. At this stage a light pre-caulk of the tapes is recommended. To produce a surface of uniform porosity the recommended method is to carry out full joint treatment, allow to dry, and texture as a one-day operation.

Caulking and Texturing

Caulk over taping and pre-caulking with caulk tool. After approximately 2 hours, apply texture coat with a laying-on brush or lambswool roller and pattern to required design. Leave to dry completely for 5 days, apply a mist coat and full coat of good quality emulsion paint for the perfect finish.

Coverage

As a general guide:

Light textures 35m² per 25kg

Heavy textures 20-30m² per 25kg

Storage

The product must be stored in temperatures above 5°C and not exceeding 30°C, in a dry place.

Shelf Life

12 months in original unopened bags if stored in the conditions listed above.

Notes

Should weather or site conditions cause uneven drying, and resulting colour irregularities can be treated simply by painting over with an almond white emulsion diluted with 25% water.

Where texturing may be delayed for an unusually long period, sealing should be carried out as soon as possible using the appropriate Instarmac primer, diluted as specified, particularly if the weather is hot and dry. To produce a surface of uniform porosity the recommended method is to carry out taping, pre-caulking and texturing as a one-day operation.

Product dries to an almond white colour.

Do not use in temperatures less than 3°C. Temperatures must also be above

Other specialist materials available from Wondertex include:

Filler and Smoother

Coving Adhesive

Plasterboard Finishing Compound

Plasterboard Joint Filler

Tools/Accessories

3°C during drying time.

Clean any accidental splashes from floors etc. with warm water before drying.

Health & Safety

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste appropriately. A full Material Safety Data Sheet relating to this product is available from www.instarmac.co.uk.

Quality Assurance

All products are manufactured in a plant whose quality management system is certified/registered as being in conformity with BS EN ISO 9001, ISO 14001 and OHSAS 18001. Wondertex products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All Wondertex products are sold subject to our conditions of sale, copies of which may be obtained upon request.

Manufactured by **Instarmac Group plc**

Danny Morson Way, Birch Coppice Business Park

Dordon, Tamworth, Staffordshire B78 1SE

Tel: +44 (0)1827 872244 Fax: +44 (0)1827 874466

Enquiries: email@instarmac.co.uk Orders: orders@instarmac.co.uk

Visit Instarmac on the web at www.instarmac.co.uk