

WONDERTEX PREM FINISH

PLASTERBOARD FINISHING COMPOUND

+ SMOOTH FINISH
+ EXTENDED WORKING TIME
+ EASY SANDING
+ NO SHRINKAGE, NO CRACKS
+ SUITABLE FOR HAND & MACHINE APPLICATION



TECHNICAL DEFINITION

Finishing compound for plasterboard joints. Designed to provide a smooth, high-quality surface prior to painting or decoration. Suitable for both manual and machine application.

SUBSTRATES

Suitable for: plasterboard joints, previously filled and prepared surfaces. Surfaces must be clean, dry, sound and free from dust.

TECHNICAL PROPERTIES

- Working time: approx. 180 minutes
- Smooth, high-quality finish
- No shrinkage, reducing risk of cracking
- Effortless sanding
- Suitable for hand and machine jointing

SAFETY

Use in well-ventilated areas. Avoid inhalation of dust during mixing. In case of contact with eyes, rinse thoroughly with water.

APPLICATION

The suggested mix ratio is 1 part water to 2 parts powder (12 litres of water per 25 kg bag). Mix thoroughly until a smooth lump free consistency is achieved, leave for 5 minutes then mix again. Apply as a finishing coat over prepared joints or surfaces. Can be applied manually or with suitable machine equipment.

STORAGE

12 months in unopened packaging in a dry place, avoiding exposure to high temperature and frost.

PACKAGING

25 kg bags.

	prem fill & finish	prem texture	prem adhesive	prem finish	prem filler
sizes	7.5kg & 15kg	25kg		25kg	12.5kg
bonding	•		•		
repairing	•			•	•
jointing	•			•	•
filling	•				•
smoothing	•	•		•	
snagging	•			•	
texturing		•			
working time	60mins	180mins	60-90mins	180mins	60-90mins
apply 2nd coat	120-250mins	n/a	n/a	3-5hours	n/a

wondertex® SEMIN GROUP

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C
Teneur en COV <1 g/L

Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk