

WONDERTEX READY MIXED JOINTING FILLER AND FINISH

+ EASY TO APPLY
+ MANUAL OR MECHANICAL USE
+ VERY FINE AND WHITE FINISH
+ EASY TO SAND

USE

MANUAL APPLICATION

MECHANICAL APPLICATION

500 g/m²
USAGE

Up to 5 mm
THICKNESS

+5 →+30° C
APPLICATION TEMPERATURE

TECHNICAL DEFINITION
Specially formulated ready-mixed filler for jointing thinned-edge plasterboards in combination with jointing paper tape.

COMPOSITION AND APPEARANCE
Resin, water, calcium carbonate, thickener, preservation agent and various adjuvants. The colour is white.

SUBSTRATES
All types of plasterboard with or without insulation (glass wool, rock wool, polystyrene) with thinned-edges and carded surfaces.
The substrate must not be frozen or overheated.
It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE
Plasterboard primer, smoothing filler.

TECHNICAL PROPERTIES
- Adhesion of tape: >1000 g.
- Density: 1.7.
- Reaction to fire: A2s1dO.

APPLICATION
Before jointing, fill any accidental gaps between boards and any other areas (spalls, deterioration of the surface, etc.).

Apply manually by filling the thinned edge using a 10 or 15 cm plaster knife and then adding the tape (milled face against the jointing filler).
Then add a finishing layer, allow to dry and finish to hide the tape. Also hide the screw heads.
For projecting vertical edges, use reinforced tape (reinforcing face on board side).
Apply a tape on the inside ceiling edges ensuring that the concrete is free of any trace of formwork oil.
The substrate must be dry and free of any powdery or insufficiently adhesive product.
Product suitable for mechanized application: Bazooka.

DRYING TIME
Second layer can be applied in 24 and 48 hours, depending on the ambient conditions.

STORAGE
12 months in original unopened packaging away from frost and high temperatures.

PACKAGING
7kg pails
20kg pails

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+
Teneur en COV <1 g/L

wondertex® SEMIN GROUP
Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk