

WONDERTEX EXTERIOR ULTRA LIGHT QUICK FILLER

+ QUICK DRYING
+ ALL SUBSTRATES, WOOD INCLUDED
+ ALL THICKNESS WITHOUT SHRINKAGE
+ WHITE MATT
+ VERY HIGH-QUALITY FINISH



TECHNICAL DEFINITION
Lightweight ready-mixed filler for all exterior repair works. Shrinkage-free and fast drying.

COMPOSITION AND APPEARANCE
Emulsion resin, lightening agent, calcium carbonate and various additives. The colour is off-white.

SUBSTRATES
Exterior walls: painted façades, masonry, rendering, brick, stone, aerated concrete, concrete, cement filler.
The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary. Cracks should be opened up before application.

COVERING AFTER USE
Can be covered with all types of filler and paint.

TECHNICAL PROPERTIES
- Density: 0.8 kg/L.
- Adhesion: >0.8 MPa in compliance with EN 16566.
- In conformity with NFT 30.608.

PRECAUTIONS FOR USE
Do not apply at a humidity level above 80%. Not suitable for use on plastic or metal. Do not inhale dust if sanding.

DRYING TIME
Depends on the substrate, weather conditions and application thickness. After filling microcracks or using water-based paints, it may be painted in 2 hours.
Wait 24 hours for acrylic paint.

STORAGE
12 months in original, unopened packaging, protected from frost and high temperatures.

PACKAGING
1 L pails

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+
Teneur en COV <1 g/L

wondertex® SEMIN GROUP
Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk