

WONDERTEX FINE SURFACE FILLER

READY-MIXED FILLER

+ EASY TO APPLY
+ SOLVENT-FREE
+ EXCELLENT ADHESION
+ VERY HIGH-QUALITY FINISH

USE

MANUAL APPLICATION

Up to 2 mm
THICKNESS

250-400 g/m²
USAGE

+8→+35° C
APPLICATION TEMPERATURE

TECHNICAL DEFINITION

Ready-mixed filler with a high resin content for interior usage on walls and ceilings. Excellent preparation before painting or the application of wall coverings. After complete drying, provides a very low absorbent finish. This means that it consumes far less paint than a standard filler. Long working time ensures the achievement of an excellent finish.

COMPOSITION AND APPEARANCE

Water-based filler with resin emulsion containing calcium carbonate, rheological agent and various additives. The resulting mix is white.

SUBSTRATES

Plasterboard, concrete, plaster blocks, cement render, primers, sanded and primed wood, finishing coating based on plaster.
The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE

Wallpaper, paint, wall coverings.

TECHNICAL PROPERTIES

- Paste density: 1.7.
- Particle size: fine.
- pH: 7.
- Adherence: in conformity with NFT 30 608.

PREPARATION OF SURFACES

If the substrates are too irregular, then first apply a smoothing compound. Smooth, brush and dust concrete panels and plaster blocks. Wash, rinse and prime old paint. Allow to set and smooth off any imperfections before sanding, if necessary. Use the primer for Fine Surface Filler before applying a gloss or satin paint.
Clean tools in water.

DRYING TIME

Approximately 12 hours depending on the thickness, the substrate and the ambient conditions.

STORAGE

12 months in unopened original packing protected from damp.

PACKAGING

1.5 kg pails
10 kg pails
20 kg pails

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+
Teneur en COV <1 g/L

wondertex® SEMIN GROUP

Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk