

WONDERTEX MASONRY REPAIR FILLER

+ EXCELLENT ADHESION
+ IDEAL FOR DETERIORATED CONCRETE
+ EASY APPLICATION
+ NO SHRINKAGE



TECHNICAL DEFINITION

Shrink-free interior-exterior repair filler with high adhesion for: filling holes and cracks, pointing, cellular concrete, repairing cornices, window reveals, sticking hinges and pins, filling facades, rough casting, building blocks.

COMPOSITION AND APPEARANCE

Cement-based powder filler containing sand, resin and various additives. The resulting mix is grey.

SUBSTRATES

Any type of clean, sound, dry, dust-free substrates free of all traces of oil: masonry, concrete cement render.
The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE

Can be covered with any type of paint, plaster-based and finishing fillers, cement or polymer render fillers.

TECHNICAL PROPERTIES

- Particle size: fine.
- pH: alkaline.
- Setting time: 40 min - 1 h 30 min.

PRECAUTIONS FOR USE

Do not apply to plaster, old paintwork and old polymer render fillers. Do not use mix that has begun to set. Do not apply to flooring. Product labelled as hazardous.
Contains cement: gloves should be worn.

MIXING

Approximately 0.45 L of water per 1.5 kg bag;
1.5 L of water per 5 kg bag;
4.5 L of water per 15 kg bag.

DRYING TIME

Depends on substrate, weather conditions and application thickness, approximately 12 hours for a 1 mm layer.

STORAGE

6 months in unopened original packing protected from damp.

PACKAGING

1.5kg bags
5kg bags
15kg bags

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C
Teneur en COV <1 g/L

wondertex® SEMIN GROUP
Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk