

WONDERTEX ULTRA LIGHT QUICK FILLER

+ QUICK DRYING
+ ALL SUBSTRATES, WOOD INCLUDED
+ ALL THICKNESS WITHOUT SHRINKAGE
+ WHITE MATT
+ VERY HIGH-QUALITY FINISH

USE

MANUAL APPLICATION

THICKNESS

USAGE
0.4 kg/m²/mm

APPLICATION TEMPERATURE
+8→+35° C

TECHNICAL DEFINITION

Ultra-light ready-mixed filler for repair of interior walls and cellings.
Shrinking-free and fast drying, ideal for high quality filling works. Very easy to use. Remains flexible after drying.
Ideal to repair micro-cracks. Allows for variations in the size of the substrate.

COMPOSITION AND APPEARANCE

Resins in emulsion with lightening agents and various additives. The colour is snow white.

SUBSTRATES

Interior walls and ceilings: plaster, masonry, cellular concrete, concrete, plasterboard, roughcast, wood, cement render.
The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary. Cracks should be opened up before application.

TECHNICAL PROPERTIES

- Density: 0.4.
- ph: 7.
- In conformity with NFT 30.608.
- Excellent application qualities.

DRYING TIME

Depends on substrate, weather conditions and application thickness.
After filling microcracks or using water-based paints, it may be painted in 2 hours.
Wait 24 hours for oil-based paint.

STORAGE

12 months in unopened original packing protected from frost and high temperatures.

PACKAGING

1 L pails
5 L pails

Made in France

ÉMISSIONS DANS L'AIR INTÉRIEUR A+
Teneur en COV <1 g/L

wondertex® SEMIN GROUP

Wilberforce House, Station Road, London NW4 4QE, England
Tel: +44 1827 934643 • wondertex.co.uk